


mulii

VERSION DE 23.1

Assembly instructions Rain cover



General

The high-quality canopy is not only very weather-resistance and robust, it can also be used flexibly. This way the spacious viewing windows allow for a view overlooking in all directions when the rain cover is closed. On sunny days, the side windows can be rolled up and at the same the UV-resistant cover protects the child from the sunlight.

A robust and reliable stainless steel rod forms the solid base for the rain cover. Quickly put together, easily installed and stored securely and compact in the supplied packing bag. This way it can also be carried away in the closed basket.

Continuously updated installation instructions are available in German and in other languages at our download portal:

<https://muli-cycles.de/de/downloads>



List of textiles used

This manual uses the following text types and lists:

- 1 Instructions (in fixed order)
- Guidelines (in any order)

Symbols / Labels used

This manual uses the following symbols and/or labels:

- ⚠ The warning triangle in combination with the word “WARNING” indicates hazards that could result in sever personal injuries or death.
- ⚠ The warning triangle in combination with the word “CAREFUL” indicates hazards that could result in slight personal injuries and property damages.
- ⓘ The circled exclamation mark indicates important additional information.

Assembly instructions

- ⚠ **WARNING! Risk of falling**
Too low handlebar height can cause the braking lever to bump into the cover. This can result in sever falls.
- After installing the cover set the handlebar height such that the handlebar, the braking lever and the cover do not collide even with full steering angle.

- ⚠ **CAUTION! Risk of injury**
A stem adapter which is extended too far can break.
- Make sure never to fix the stem adapter for the ride above the MIN/MAX marking shown in Fig. 1. The maximum extension position is merely for turning the handlebar in the park situations.




FIG. 1

- 1 Loosen the handlebar quick release and take the handlebar in the upper position up to the maximum extension marking. (Fig. 2)
- 2 Put the frame rods together. (Fig. 3)
- 3 Insert the large rods in the two front frame holders and the small rods in the two rear holders. (Fig. 4)

⚠ CAUTION! Risk of breakage
Inserting the bows in the holder can create a large leverage force on the rod which can bend the bows if force is applied.

→ Avoid large horizontal pressure on the metal bows if they are inserted in the holder.

- 4 Pull the rain cover from the front over the frame rods. In doing so, make sure that it is placed at the front over the basket basin. Only then can it be pulled with slight force at the back over the basket stopper. (Fig. 5)



FIG. 2



FIG. 3



FIG. 4



FIG. 5

- 5 Then, insert the cover over the steering side bows and pull it left and right over the basket stopper. (Fig. 6)
- 6 Slide the handlebar tension rope of the rain cover under the pipe on which the basket sits and fix it in the holder. (Fig. 7)
- 7 Finally, tighten the rain cover at the front by passing the elastic band under the frames on the steering pipe and clicking in the cover. (Fig. 8)
- 8 The position of the handlebar can now be changed again and adjusted to the desired riding position. The handlebar should never be fixed above the max. position for riding. At the same time, the handlebar should rotate freely over the cover - see Instructions page 5.



FIG. 6




FIG. 7




FIG. 8

Rolling up the window

The window of the rain cover can be rolled up and fixed in rolled-up position. In warm days, this provides children with sun protection from above and fresh air from the sides. There is also a small loop on the inner side of the window for winding up to half height.

- 1 Open the zipper on both sides of the window and roll up the window compact with both hands. (Fig. 9)
- 2 Hold the band which is fixed to the inside of the cover and slide the loop around the toggle on the outer side of the canopy. (Fig. 10)

⚠ Make sure to tuck the bands in the pocket on the inside of the canopy if not used.

- 3 The cover is not rolled for fixing the window at half height. There is a loop on the inside of the window. Hook this loop in the toggle on the outside of the canopy. Pull the zipper to the corresponding half-opening position. (Fig. 11)



FIG. 9



FIG. 11



FIG. 10

Folding instructions

⚠ CAUTION! Risk of breakage
Incorrect or too frequent folding can result in cracks in the transparent window material.

→ Make sure to follow the folding instructions when you fold the cover for storage.

Please read these folding instructions carefully and remember the folding steps.

- 1 Place the cover on a flat surface. First, put it together as shown. Make sure the window material is not at the edge on the sides but terminates at the edge of the black textile. (Fig. 12)
- 2 Then, fold the side tips. (Fig. 13)
- 3 Fold the entire cover about in the middle. (Fig. 14)
- 4 Fold the cover a second time by half, at 90° angle to the first folding. (Fig. 15)
- 5 Now you can store the cover including the metal bows in the supplied bag and obtain a compact pack size. (Fig. 16)



FIG. 12




FIG. 13




FIG. 14



FIG. 15




FIG. 16



Legal notice

BA-EX-12V23.1
©muli cycles GmbH

Widdersdorfer Str. 190
50825 Köln

Text and graphics
muli cycles GmbH

Photography
Tim Kaiser

Layout
Friederike Wolf, Frieder Oelze

Production
Misprint, Erfurt

Paper
Circleoffset Premium White (FSC-certified, awarded the blue environmental angel and EU Ecolabel)

www.muli-cycles.de